

# HF3FF

# SUBMINIATURE HIGH POWER RELAY



File No.:E134517



File No.:40025218



File No.:R50148356



File No.:CQC13002098175  
CQC16002140467



## Features

- 15A 125VAC、10A 250VAC switching capability
- 1 Form A and 1 Form C configurations
- Subminiature, standard PCB layout
- Plastic sealed and flux proofed types available
- UL insulation system: Class F

## CONTACT DATA

Contact arrangement	1A	1C	
		NO	NC
Contact resistance <sup>1)</sup>	100mΩ max.(at 1A 6VDC)		
Contact material	AgSnO <sub>2</sub> , AgCdO		
Contact rating (Res. load)	10A 277VAC 10A 28VDC	10A 277VAC <sup>2)</sup> 10A 28VDC <sup>2)</sup>	5A 250VAC
Max. switching voltage	277VAC / 28VDC		250VAC
Max. switching current	15A	10A	5A
Max. switching power	2770VA / 280W		1250VA
Mechanical endurance	1 x 10 <sup>7</sup> OPS		
Electrical endurance <sup>3)</sup>	1H type: 1x 10 <sup>5</sup> OPS (10A 250VAC, Resistive load, Room temp., 1s on 9s off) 1Z type: 5 x 10 <sup>4</sup> OPS (NO: 5A/NC: 5A 250VAC, Resistive load, Room temp., 5s on 5s off)		

- Notes:** 1) The data shown above are initial values.  
2) Applicable when NC is not energized with load.  
3) For plastic sealed type, the venting-hole should be opened in electrical endurance test.

## CHARACTERISTICS

Insulation resistance	100MΩ (at 500VDC)	
Dielectric strength	Between coil & contacts	1500VAC 1min
	Between open contacts	750VAC 1min
Operate time (at rated. volt.)	10ms max.	
Release time (at rated. volt.)	5ms max.	
Shock resistance	Functional	98m/s <sup>2</sup>
	Destructive	980m/s <sup>2</sup>
Vibration resistance	10Hz to 55Hz 1.5mm DA	
Humidity	5% to 85% RH	
Ambient operating temperature	-40°C to 105°C	
Termination	PCB	
Unit weight	Approx. 10g	
Construction	Plastic sealed, Flux proofed	

- Notes:** 1) The data shown above are initial values.  
2) If the ambient temperature is higher than 85°C, please contact with Hongfa.  
3) For plastic sealed type, the venting-hole should be opened in electrical endurance test.

## COIL

Coil power	5VDC to 24VDC: Approx. 360mW; 48VDC: Approx. 510mW
------------	---

## COIL DATA

at 23°C

Nominal Voltage VDC	Pick-up Voltage VDC max. <sup>1)</sup>	Drop-out Voltage VDC min. <sup>1)</sup>	Max. Voltage VDC * <sup>3)</sup>	Coil Resistance Ω
5	3.80	0.5	6.5	70 x (1±10%)
6	4.50	0.6	7.8	100 x (1±10%)
9	6.80	0.9	11.7	225 x (1±10%)
12	9.00	1.2	15.6	400 x (1±10%)
18	13.5	1.8	23.4	900 x (1±10%)
24	18.0	2.4	31.2	1600 x (1±10%)
48	36.0	4.8	62.4	4500 x (1±10%)
48 <sup>1)</sup>	36.0	4.8	62.4	6400 x (1±10%)

- Notes:** 1) The data shown above are initial values.  
2) There are 2 types for 48V-510mW and 360mW. The coil resistance for 510mW type is 4500ohm while for that for 360mW type is 6400ohm. If 360mW type is required, please add a special suffix (068) in the ordering information.  
3) \*Maximum voltage refers to the maximum voltage which relay coil could endure in a short period of time.

## SAFETY APPROVAL RATINGS

UL/CUL	1 Form A	10A 277VAC 10A 28VDC 15A 125VAC 6A 250VAC 1/2HP 125VAC (AgSnO <sub>2</sub> )
	1 Form C	NO:10A 277VAC NO:10A 28VDC NO:10A 120VAC NO:6A 250VAC NC:10A 120VAC
VDE (only AgSnO <sub>2</sub> )	1 Form A	10A 250VAC 12A 125VAC
	1 Form C	NO/NC:5A/5A 250VAC NO:10A 250VAC NO:12A 125VAC

- Notes:** 1) Only typical loads are listed above. Other load specifications can be available upon request.  
2) For sealed type, the vent-hole cover should be excised.



HONGFA RELAY

ISO9001, ISO/TS16949, ISO14001, OHSAS18001, IECQ QC 080000 CERTIFIED

2019 Rev. 1.06


## ORDERING INFORMATION

<b>HF3FF / 012 -1H S T F (XXX)</b>			
<b>Type</b>			
<b>Coil voltage</b>	5, 6, 9, 12, 18, 24, 48VDC		
<b>Contact arrangement</b>	<b>1H:1 Form A</b>	<b>1Z:1 Form C</b>	
<b>Construction<sup>1) 2)</sup></b>	<b>S: Plastic sealed</b>	<b>Nil: Flux proofed</b>	
<b>Contact material</b>	<b>T: AgSnO<sub>2</sub></b>	<b>Nil: AgCdO</b>	
<b>Insulation standard</b>	<b>F: Class F</b>		
<b>Special code<sup>3)</sup></b>	<b>XXX: Customer special requirement</b>	<b>Nil: Standard</b>	

- Notes:** 1) We recommend flux proofed types for a clean environment (free from contaminations like H<sub>2</sub>S, SO<sub>2</sub>, NO<sub>2</sub>, dust, etc.). We suggest to choose plastic sealed types and validate it in real application for an unclean environment (with contaminations like H<sub>2</sub>S, SO<sub>2</sub>, NO<sub>2</sub>, dust, etc).
- 2) Contact is recommended for suitable condition and specifications if water cleaning or surface process is involved in assembling relays on PCB.
- 3) The customer special requirement express as special code after evaluating by Hongfa.
- 4) Two packing methods available: paper box package, tube package, Standard tube packing length is 328mm. Any special requirement needed, please contact us for more details.

## OUTLINE DIMENSIONS, WIRING DIAGRAM AND PC BOARD LAYOUT


Unit: mm




- Remark: 1) In case of no tolerance shown in outline dimension: outline dimension  $\leq 1$ mm, tolerance should be  $\pm 0.2$ mm; outline dimension  $> 1$ mm and  $\leq 5$ mm, tolerance should be  $\pm 0.3$ mm; outline dimension  $> 5$ mm, tolerance should be  $\pm 0.4$ mm.
- 2) The additional tin top is max. 1mm.
- 3) The tolerance without indicating for PCB layout is always  $\pm 0.1$ mm.

## CHARACTERISTIC CURVES


MAXIMUM SWITCHING POWER



ENDURANCE CURVE



COIL TEMPERATURE RISE



**Test conditions:**

NO, Resistive load, 277VAC/28VDC,  
Flux proofed, Room temp., 1s on 9s off  
CO, Resistive load, 250VAC,  
Flux proofed, Room temp., 5s on 5s off.

**Notes:**For plastic sealed type,the venting-hole should be opened in electrical endurance test.

**Testing conditions:**

10A at 85°C.  
Mounting distance: 10mm

**Disclaimer**

The specification is for reference only. See to "Terminology and Guidelines" for more information. Specifications subject to change without notice. We could not evaluate all the performance and all the parameters for every possible application. Thus the user should be in a right position to choose the suitable product for their own application. If there is any query, please contact Hongfa for the technical service. However, it is the user's responsibility to determine which product should be used only.

© Xiamen Hongfa Electroacoustic Co., Ltd. All rights of Hongfa are reserved.