# Product data sheet Characteristics

## RXZE2M114M

Socket, mixed contact, relay type RXM2 RXM4, connector connection, 250 V AC





#### Main

Range of product	Zelio Relay	
Product or component type	Socket	
Contact terminal arrangement	Mixed	
Product compatibility	Plug-in relay RXM with 2 C/O contact Plug-in relay RXM with 4 C/O contact	
Shape of pin	Flat	
Device short name	RXZ	
Sale per indivisible quantity	10	

#### Complementary

th cable end n cable end out cable end out cable end
_

#### Environment

IEC 61984	
UL CSA Lloyd's	
-4085 °C	
-4055 °C	
IP20 conforming to EN/IEC 60529	
2500 V	
	UL CSA Lloyd's -4085 °C -4055 °C IP20 conforming to EN/IEC 60529

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	54 G
Package 1 Height	4.3 Cm
Package 1 width	2.7 Cm
Package 1 Length	8 Cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	574 Kg
Package 2 Height	7.7 Cm
Package 2 width	9.2 Cm
Package 2 Length	14.2 Cm
Unit Type of Package 3	S02
Number of Units in Package 3	120
Package 3 Weight	30.52 Kg
Package 3 Height	15 Cm
Package 3 width	30 Cm
Package 3 Length	40 Cm

## Offer Sustainability

Sustainable offer status	Green Premium product	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEL RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	€Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

### Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : Commercialised