

SIMATIC DP, Electronics module f. ET200S, 2AI Standard I-2DMU  
 15 mm width, 4.. 20mA; 13 bit for 2-wire transducer Cycle time 65  
 ms/channel with SF LED (group fault)



Supply voltage	
Load voltage L+	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> <li>Reverse polarity protection</li> </ul>	24 V; From power module Yes; Destruction limit 35 mA per channel
Input current	
from load voltage L+ (without load), max.	80 mA
from backplane bus 3.3 V DC, max.	10 mA
Power loss	
Power loss, typ.	0.6 W
Address area	
Address space per module	
<ul style="list-style-type: none"> <li>Address space per module, max.</li> </ul>	4 byte
Analog inputs	
Number of analog inputs	2
permissible input current for current input (destruction limit), max.	40 mA
Cycle time (all channels) max.	Number of active channels per module x basic conversion time

<b>Input ranges (rated values), currents</b>	
• 4 mA to 20 mA	Yes; on 50 ohms
<b>Cable length</b>	
• shielded, max.	200 m
<b>Analog value generation for the inputs</b>	
<b>Integration and conversion time/resolution per channel</b>	
• Resolution with overrange (bit including sign), max.	13 bit; 4 to 20 mA: 13 bit
• Integration time (ms)	16,7 / 20 ms
• Interference voltage suppression for interference frequency f1 in Hz	50 / 60 Hz
• Conversion time (per channel)	65 ms; 55 / 65 ms
<b>Errors/accuracies</b>	
<b>Operational error limit in overall temperature range</b>	
• Current, relative to input range, (+/-)	0.6 %
<b>Basic error limit (operational limit at 25 °C)</b>	
• Current, relative to input range, (+/-)	0.4 %
<b>Interrupts/diagnostics/status information</b>	
<b>Diagnoses</b>	
• Wire-break	Yes
• Group error	Yes
• Overflow/underflow	Yes
<b>Diagnostics indication LED</b>	
• Group error SF (red)	Yes
<b>Parameter</b>	
Remark	4 byte
Measurement type/range	deactivated / 4 to 20 mA
Group diagnostics	Disable / enable
Overflow/underflow	Disable / enable
<b>Potential separation</b>	
<b>Potential separation analog inputs</b>	
• between the channels	No
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	No
<b>Isolation</b>	
Isolation tested with	500 V DC
<b>Dimensions</b>	
Width	15 mm
Height	81 mm
Depth	52 mm

## Weights

Weight, approx.

40 g

**last modified:**

09/03/2020