

SIMATIC S7-300, temperature Control Unit FM 355-2 C, 4 channels, continuous, 4 AI+8 DI+4 AO incl. multi-language configuration package, Manual and Getting Started (de, de, fr, en it) on CD-ROM



Figure similar

### Supply voltage

#### Load voltage L+

• Rated value (DC)	24 V
• permissible range, lower limit (DC)	20.4 V
• permissible range, upper limit (DC)	28.8 V

### Input current

from load voltage L+ (without load), max.	310 mA; Typ. 260 mA
from backplane bus 5 V DC, max.	75 mA; typ. 50 mA

### Power loss

Power loss, typ.	6.5 W
Power loss, max.	7.8 W

### Digital inputs

Number of digital inputs	8
Input characteristic curve in accordance with IEC 61131, type 2	Yes

#### Input voltage

• Rated value (DC)	24 V
• for signal "0"	-3 to +5V
• for signal "1"	13 to 30V
<b>Input current</b>	
• for signal "1", typ.	7 mA
<b>Cable length</b>	
• shielded, max.	1 000 m
• unshielded, max.	600 m
<b>Analog inputs</b>	
Number of analog inputs	4
permissible input voltage for voltage input (destruction limit), max.	20 V
permissible input current for current input (destruction limit), max.	40 mA
<b>Input ranges</b>	
• Voltage	Yes
• Current	Yes
• Thermocouple	Yes
• Resistance thermometer	Yes
<b>Input ranges (rated values), voltages</b>	
• 0 to +10 V	Yes
— Input resistance (0 to 10 V)	100 k $\Omega$
• -1.75 V to +11.75 V	Yes
— Input resistance (-1.75 V to +11.75 V)	100 k $\Omega$
<b>Input ranges (rated values), currents</b>	
• 0 to 20 mA	Yes
— Input resistance (0 to 20 mA)	50 $\Omega$
• 0 to 23.5 mA	Yes
— Input resistance (0 to 23.5 mA)	50 $\Omega$
• -3.5 mA to +23.5 mA	Yes
— Input resistance (-3.5 mA to +23.5 mA)	50 $\Omega$
• 4 mA to 20 mA	Yes
— Input resistance (4 mA to 20 mA)	50 $\Omega$
<b>Input ranges (rated values), thermocouples</b>	
• Type B	Yes
— Input resistance (Type B)	10 M $\Omega$
• Type E	Yes
— Input resistance (Type E)	10 M $\Omega$
• Type J	Yes
— Input resistance (type J)	10 M $\Omega$
• Type K	Yes
— Input resistance (Type K)	10 M $\Omega$

• Type R	Yes
— Input resistance (Type R)	10 M $\Omega$
• Type S	Yes
— Input resistance (Type S)	10 M $\Omega$
<b>Input ranges (rated values), resistance thermometer</b>	
• Pt 100	Yes
— Input resistance (Pt 100)	10 M $\Omega$
<b>Thermocouple (TC)</b>	
<b>Temperature compensation</b>	
— internal temperature compensation	Yes
— external temperature compensation with Pt100	Yes
<b>Characteristic linearization</b>	
• parameterizable	Yes
— for thermocouples	Type B, E, J, K, R, S
— for resistance thermometer	Pt100 (standard)
<b>Cable length</b>	
• shielded, max.	200 m; 50 m at 80 mV and thermocouples
<b>Analog outputs</b>	
Number of analog outputs	4
Voltage output, short-circuit protection	Yes
Voltage output, short-circuit current, max.	25 mA
Current output, no-load voltage, max.	18 V
<b>Output ranges, voltage</b>	
• 0 to 10 V	Yes
• -10 V to +10 V	Yes
<b>Output ranges, current</b>	
• 0 to 20 mA	Yes
• 4 mA to 20 mA	Yes
<b>Connection of actuators</b>	
• for voltage output two-wire connection	Yes
• for current output two-wire connection	Yes
<b>Load impedance (in rated range of output)</b>	
• with voltage outputs, min.	1 k $\Omega$
• with voltage outputs, capacitive load, max.	1 $\mu$ F
• with current outputs, max.	500 $\Omega$
• with current outputs, inductive load, max.	1 mH
<b>Cable length</b>	
• shielded, max.	200 m; 50 m at 80 mV and thermocouples
<b>Analog value generation for the inputs</b>	
Integration and conversion time/resolution per channel	

- Resolution with overrange (bit including sign), max. 14 bit

### Analog value generation for the outputs

#### Settling time

- for resistive load 0.1 ms
- for capacitive load 3.3 ms
- for inductive load 0.5 ms

### Encoder

#### Connection of signal encoders

- for voltage measurement Yes
- for current measurement as 4-wire transducer Yes

#### Connectable encoders

- 2-wire sensor Yes
- permissible quiescent current (2-wire sensor), max. 1.5 mA

### Errors/accuracies

#### Operational error limit in overall temperature range

- Voltage, relative to input range, (+/-) 0.6 %;  $\pm 0.6$  to  $\pm 0.7$  %
- Current, relative to input range, (+/-) 0.6 %;  $\pm 0.6$  to  $\pm 0.7$  %
- Resistance thermometer, relative to input range, (+/-) 0.6 %;  $\pm 0.6$  to  $\pm 0.7$  %
- Voltage, relative to output range, (+/-) 0.5 %
- Current, relative to output range, (+/-) 0.6 %

#### Basic error limit (operational limit at 25 °C)

- Voltage, relative to input range, (+/-) 0.04 %;  $\pm 0.04$  to  $\pm 0.5$  %
- Current, relative to input range, (+/-) 0.04 %;  $\pm 0.04$  to  $\pm 0.5$  %
- Resistance thermometer, relative to input range, (+/-) 0.04 %;  $\pm 0.04$  to  $\pm 0.5$  %
- Voltage, relative to output range, (+/-) 0.4 %
- Current, relative to output range, (+/-) 0.5 %

### Interrupts/diagnostics/status information

- Substitute values connectable Yes; Parameterizable

### Integrated Functions

- Counter No

#### Control technology

- Number of closed-loop controllers 4

### Potential separation

#### Potential separation controller

- between the channels No
- between the channels and backplane bus Yes; Optocoupler

## Isolation

Isolation tested with	500 V DC
-----------------------	----------

## Connection method

required front connector	2x 20-pin
--------------------------	-----------

## Dimensions

Width	80 mm
-------	-------

Height	125 mm
--------	--------

Depth	120 mm
-------	--------

## Weights

Weight, approx.	470 g
-----------------	-------

<b>last modified:</b>	09/03/2020
-----------------------	------------