

### Product type designation

### CP 443-5 Extended

Communications processor CP 443-5 Extended for connection of SIMATIC S7-400 to PROFIBUS DP, S5-compatible, PG/OP and S7 communication



### Transfer rate

#### Transfer rate

- at the 1st interface / acc. to PROFIBUS

9.6 kbit/s ... 12 Mbit/s

### Interfaces

Number of interfaces / acc. to Industrial Ethernet

0

Number of electrical connections

- at the 1st interface / acc. to PROFIBUS

1

Type of electrical connection

- at the 1st interface / acc. to PROFIBUS

9-pin Sub-D socket (RS485)

### Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage

DC

Supply voltage / 1 / from backplane bus

5 V

Relative symmetrical tolerance / at DC

- at 5 V

5 %

Consumed current

- from backplane bus / at DC / at 5 V / typical

0.6 A

Power loss [W]

3 W

Ambient conditions	
Ambient temperature	
<ul style="list-style-type: none"> <li>during operation</li> </ul>	0 ... 60 °C
<ul style="list-style-type: none"> <li>during storage</li> </ul>	-40 ... +70 °C
<ul style="list-style-type: none"> <li>during transport</li> </ul>	-40 ... +70 °C
Relative humidity	
<ul style="list-style-type: none"> <li>at 25 °C / without condensation / during operation / maximum</li> </ul>	95 %
Protection class IP	IP20

Design, dimensions and weights	
Module format	Compact module S7-400 single width
Width	25 mm
Height	290 mm
Depth	210 mm
Net weight	0.65 kg

Product features, product functions, product components / general	
Number of units	
<ul style="list-style-type: none"> <li>per CPU / maximum</li> </ul>	14
<ul style="list-style-type: none"> <li>Note</li> </ul>	The number of CPs that can be operated as DP masters depends on the number of CP 443-1 Advanced processors operating in the S7-400 station as PROFINET IO controllers. Up to 10 CPs can be operated in total: up to 4 as PROFINET IO controllers (CP 443-1 Advanced); up to 10 as DP masters (CP 443-5 Extended)

Performance data / open communication	
Number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	32
Amount of data	
<ul style="list-style-type: none"> <li>as user data per connection / for open communication / by means of SEND/RECEIVE blocks / maximum</li> </ul>	240 byte

Performance data / PROFIBUS DP	
Service / as DP master	
<ul style="list-style-type: none"> <li>DPV1</li> </ul>	Yes
Number of DP slaves	
<ul style="list-style-type: none"> <li>on DP master / usable</li> </ul>	125
Amount of data	
<ul style="list-style-type: none"> <li>of the address area of the inputs / as DP master / total</li> </ul>	4096 byte
<ul style="list-style-type: none"> <li>of the address area of the outputs / as DP master / total</li> </ul>	4096 byte
<ul style="list-style-type: none"> <li>of the address area of the inputs / per DP slave</li> </ul>	244 byte

- of the address area of the outputs / per DP slave

244 byte

#### Performance data / S7 communication

Number of possible connections / for S7 communication

- maximum

48

#### Performance data / multi-protocol mode

Number of active connections / with multi-protocol mode

- without DP / maximum
- with DP / maximum

59

54

#### Product functions / management, configuration, engineering

Configuration software

- required

STEP 7 V5.4 SP4 or higher / STEP 7 Professional V12 (TIA Portal) or higher

#### Further information / Internet-Links

Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/snst>

<http://www.siemens.com/simatic-net>

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

#### Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

07/13/2020